

KONICA MINOLTA C224e

Configuration Page

Print Operation Menu Map

Basic Setting

Default Paper Size	=	8 1/2x11
Default Paper Type	=	Not Specified
Paper Tray	=	Auto
Output Tray	=	Elevate Tray
Binding Position	=	Left Binding
Double-Sided	=	Off
Staple	=	Off
Hole-Punch	=	Off
Orientation	=	Portrait
# of Sets	=	1
No Matching Paper in Tray Setting	=	Stop Printing (Tray Fixed)
Spool Setting	=	On
Convert	=	Off
PDL Setting	=	Auto
Banner Setting	=	Disable
Banner Paper Tray	=	Auto
Color Settings	=	Document
Glossy Mode	=	Off
Toner Save	=	Off
Edge Enhancement	=	Off

PCL Setting

Font Source	=	1
Font Number	=	0
Font Point	=	12.00
Font Pitch	=	10.00
Symbol Set	=	Roman-8
Line/Page	=	60 [Line / Page]
CR/LF Mapping	=	Off
Select Color	=	Auto Color
Thin Line Support	=	On

PS Setting

Print Reports	=	Disable
Text RGB Source	=	4
Text Destination Profile	=	Auto
Image RGB Source	=	4
Image Destination Profile	=	Auto
Graphics RGB Source	=	4
Graphics Destination Profile	=	Auto
Simulation Profile	=	21
Select Color	=	Auto Color

XPS Settings

Verify XPS Digital Signature	=	Disable
------------------------------	---	---------

Test Print

Configuration
PCL Font List
PS Font List
Demo Page

I/F Setting

Network Rx Timeout	=	60 [sec.]
USB Timeout	=	60 [sec.]
Print XPS Errors	=	Enable

Installed

Printer HDD	=	Installed
Printer Memory	=	2304 [MByte]

Printer Information

Installed Tray

Tray 1	=	8 1/2x11
Tray 2	=	8 1/2x14
Tray 3	=	None
Tray 4	=	None
LCT	=	8 1/2x11

Option

Duplex Unit	=	Installed
Finisher	=	Not Available
Punch Unit	=	Not Available
Fold Unit	=	Not Available
Fax Unit	=	Available
Mailbin Unit	=	Not Available

Firmware Version

Management Version	=	7
Printer Controller	=	A5C10Y0-3000-G01-43

Network

MAC Address

MAC Address	=	00:20:6B:97:EC:CE
-------------	---	-------------------

TCP/IP

TCP/IP	=	Enable
IP Address	=	192.168.0.154 (Search)
Subnet Mask	=	255.255.255.0
Default Gateway	=	192.168.0.1
RAW Port 0	=	9100
RAW Port 1	=	9112
RAW Port 2	=	9113
RAW Port 3	=	9114
RAW Port 4	=	9115
RAW Port 5	=	9116

Netware

Netware	=	Disable
---------	---	---------

Appletalk

Appletalk	=	Enable
-----------	---	--------

SMB

SMB	=	Disable
-----	---	---------

• Switch from public user
to Admin
• login

- Admin password - 1-8 (1,2,3,4,5,6,7,8)
- Store address
- New reg